

according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 1 of 10

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

WP 2-K EPOXY-TURBO (Part A)

UFI: 9ERV-C5W1-V30C-57TU

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives and sealants

## 1.3. Details of the supplier of the safety data sheet

Company name: Werkstatt-Produkte GmbH Street: Hahnerberger Str. 175 Place: 42349 Wuppertal

Telephone: +49 (0) 202 - 495839-0 Telefax: +49 (0) 202 - 495839-10

e-mail: info@werkstatt-produkte.de Internet: www.werkstatt-produkte.de

**1.4. Emergency telephone** +49 (0) 89-19240 (24h) (deutsch und englisch)

number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

# Regulation (EC) No 1272/2008

# Hazard components for labelling

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Signal word: Warning

Pictograms:





#### **Hazard statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eve irritation.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P391 Collect spillage.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 2 of 10

#### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Resulting from the use of the product: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) Contains epoxy constituents. May produce an allergic reaction.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name			Quantity	
	EC No	EC No Index No REACH No			
	Classification (Regulation (EC) No 1272/2008)				
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]p	bis-[4-(2,3-epoxipropoxi)phenyl]propane			
	216-823-5 603-073-00-2 01-2119456619-26				
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411				

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	ecific Conc. Limits, M-factors and ATE	
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxi)phenyl]propane	95 - 100 %
	Skin Irrit. 2; H315: >= 5 - 100		

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

# After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

## After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician.

## After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

# After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

## 4.2. Most important symptoms and effects, both acute and delayed

Allergic reactions

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 3 of 10

## 5.1. Extinguishing media

## Suitable extinguishing media

Foam, Carbon dioxide (CO2), Dry extinguishing powder Co-ordinate fire-fighting measures to the fire surroundings.

## Unsuitable extinguishing media

Full water jet

## 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO2))

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

## For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

#### For emergency responders

Personal protection equipment: see section 8

## 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

## 6.3. Methods and material for containment and cleaning up

### For containment

Stop leak if safe to do so. Cover drains.

## For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

## Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

## Advice on protection against fire and explosion

Usual measures for fire prevention.

### Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 4 of 10

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Keep away from: Food and feedingstuffs

Protect from direct sunlight.

Do not store together with: Oxidizing agent, Acids

## Further information on storage conditions

Recommended storage temperature: -18 - 5 °C

#### 7.3. Specific end use(s)

Adhesives and sealants (Multi-component adhesives and sealants)

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### Additional advice on limit values

To date, no national critical limit values exist.

## 8.2. Exposure controls









## Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

# Individual protection measures, such as personal protective equipment

## Eye/face protection

Wear eye/face protection. (EN 166)

#### Hand protection

Wear suitable gloves. (EN ISO 374)

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material: > 0,2mm

Permeation time (maximum wear duration): > 120 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

## Skin protection

Wear suitable protective clothing.

# Respiratory protection

In case of inadequate ventilation wear respiratory protection. (EN 14387) Filter type: A

## Thermal hazards

No information available.

## **Environmental exposure controls**

Avoid release to the environment.



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 5 of 10

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear

Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range:

Flammability: Non-flammable. Lower explosion limits: not determined Upper explosion limits: not determined 266 °C Flash point: Auto-ignition temperature: not determined Decomposition temperature: not determined pH-Value: not determined Viscosity / kinematic: not determined Water solubility: not determined

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative vapour density:

Particle characteristics:

not determined

not determined

not determined

not determined

not applicable

# 9.2. Other information

No information available.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Reaction with: Oxidizing agent, Strong acid, Alkali (lye), Amines

# 10.4. Conditions to avoid

Protect against: Heat Protect from direct sunlight.

## 10.5. Incompatible materials

Information is given in subsection 10.3.

# 10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO2))

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

Based on available data, the classification criteria are not met.

#### Werkstatt-Produkte GmbH



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 6 of 10

## Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. (bis-[4-(2,3-epoxipropoxi)phenyl]propane)

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

# 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

No information available.

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

Avoid release to the environment.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

## **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## List of Wastes Code - residues/unused products



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 7 of 10

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS

(PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances;

hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

# **SECTION 14: Transport information**

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BISPHENOL-A DIGLYCIDYLETHER)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:



9

Ш

Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BISPHENOL-A DIGLYCIDYLETHER)

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label:



Ш

9

Classification code: M6

Special Provisions: 274 335 375 601

Limited quantity: 5 L Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BISPHENOL-A DIGLYCIDYLETHER)

14.3. Transport hazard class(es):

14.4. Packing group:



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 8 of 10

Hazard label:

9

Special Provisions: 274 335 969

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082

**14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(BISPHENOL-A DIGLYCIDYLETHER)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: A97 A158 A197 A215

Limited quantity Passenger: 30 kg G Passenger LQ: Y964 Excepted quantity: E1

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: bis-[4-(2,3-epoxipropoxi)phenyl]propane

# 14.6. Special precautions for user

No information available.

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): 0 %

Information according to 2012/18/EU

(SEVESO III):

E2 Hazardous to the Aquatic Environment

# **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under

the Maternity Protection Directive (92/85/EEC) for expectant or nursing

mothers.



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 9 of 10

Water hazard class (D): 2 - obviously hazardous to water

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

## Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

# Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.





according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part A)

Revision date: 26.06.2023 Product code: 7011585101 Page 10 of 10

H411

Toxic to aquatic life with long lasting effects.

## **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

#### Werkstatt-Produkte GmbH



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 1 of 10

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

WP 2-K EPOXY-TURBO (Part B)

UFI: K8SV-E5T0-X309-SNNG

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesives and sealants

## 1.3. Details of the supplier of the safety data sheet

Company name: Werkstatt-Produkte GmbH Street: Hahnerberger Str. 175 Place: 42349 Wuppertal

Telephone: +49 (0) 202 - 495839-0 Telefax: +49 (0) 202 - 495839-10

e-mail: info@werkstatt-produkte.de Internet: www.werkstatt-produkte.de

**1.4. Emergency telephone** +49 (0) 89-19240 (24h) (deutsch und englisch)

number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

## Regulation (EC) No 1272/2008

## Hazard components for labelling

2,4,6-tris(dimethylaminomethyl)phenol

Signal word: Warning

Pictograms:



# **Hazard statements**

H302 Harmful if swallowed. H315 Causes skin irritation.

H319 Causes serious eye irritation.

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 2 of 10

#### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. Resulting from the use of the product: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700) Contains epoxy constituents. May produce an allergic reaction.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
90-72-2	2,4,6-tris(dimethylaminomethyl)	2,4,6-tris(dimethylaminomethyl)phenol		
	202-013-9	603-069-00-0	01-2119560597-27	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H302 H315 H319			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	95 - 100 %
	oral: LD50 =	oral: LD50 = 1916 - < 2455 mg/kg	

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

## After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

## After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician.

## After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

## After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 3 of 10

#### Suitable extinguishing media

Foam, Carbon dioxide (CO2), Dry extinguishing powder Co-ordinate fire-fighting measures to the fire surroundings.

# Unsuitable extinguishing media

Full water iet

# 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO2))

# 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

## For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

## For emergency responders

Personal protection equipment: see section 8

# 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

## 6.3. Methods and material for containment and cleaning up

#### For containment

Stop leak if safe to do so. Cover drains.

## For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

Clean contaminated articles and floor according to the environmental legislation.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

## Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

# Advice on protection against fire and explosion

Usual measures for fire prevention.

## Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

# 7.2. Conditions for safe storage, including any incompatibilities



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 4 of 10

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# Hints on joint storage

Keep away from: Food and feedingstuffs

Protect from direct sunlight.

Do not store together with: Oxidizing agent, Acids

# Further information on storage conditions

Recommended storage temperature: 5 - 25°C

## 7.3. Specific end use(s)

Adhesives and sealants (Multi-component adhesives and sealants)

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **DNEL/DMEL values**

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol			
Worker DNEL	, acute	dermal	systemic	0,6 mg/kg bw/day
Worker DNEL	, long-term	dermal	systemic	0,15 mg/kg bw/day
Worker DNEL	, acute	inhalation	systemic	2,1 mg/m³
Worker DNEL	, long-term	inhalation	systemic	0,53 mg/m³
Consumer DN	EL, long-term	oral	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	0,075 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,075 mg/kg bw/day
Consumer DN	Consumer DNEL, acute		systemic	0,13 mg/m³
Consumer DNEL, long-term		inhalation	systemic	0,13 mg/m³

## **PNEC** values

CAS No	Name of agent	
Environmental	compartment	Value
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	
Freshwater		0,046 mg/l
Marine water 0,005 mg		0,005 mg/l
Freshwater sediment 0,262 mg/k		0,262 mg/kg
Marine sediment		0,026 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,2 mg/l
Soil 0,025 mg/kg		0,025 mg/kg

# Additional advice on limit values

To date, no national critical limit values exist.

# 8.2. Exposure controls



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 5 of 10









#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

# Individual protection measures, such as personal protective equipment

## Eye/face protection

Wear eye/face protection. (EN 166)

### Hand protection

Wear suitable gloves. (EN ISO 374)

By long-term hand contact

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: > 0,7mm

Permeation time (maximum wear duration): > 480 min.

By short-term hand contact

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: > 0,7mm

Permeation time (maximum wear duration): > 120 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

## Skin protection

Wear suitable protective clothing.

# Respiratory protection

In case of inadequate ventilation wear respiratory protection. (EN 14387) Filter type: A-P1

#### Thermal hazards

No information available.

# **Environmental exposure controls**

Avoid release to the environment.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid (Paste)
Colour: light yellow
Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

225 °C

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

not determined

Flash point:

Auto-ignition temperature:

Decomposition temperature:

> 100 °C

not determined

> 100 °C

> 100 °C

> 100 °C



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 6 of 10

pH-Value: not determined Viscosity / kinematic: not determined Water solubility: partially miscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density:

Relative vapour density:

Particle characteristics:

not determined

1,12 g/cm³

not determined

not determined

not determined

not applicable

#### 9.2. Other information

No information available.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Reaction with: Oxidizing agent, Strong acid, Alkali (lye), Amines, Peroxides, Mixtures of sodium hypochlorite

## 10.4. Conditions to avoid

Protect against: Heat Protect from direct sunlight.

# 10.5. Incompatible materials

Information is given in subsection 10.3.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO2))

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

Harmful if swallowed.

## **ATEmix calculated**

ATE (oral) 1916,0 mg/kg

CAS No	Chemical name				
	Exposure route Dose Species Source Method				
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol				
	oral	LD50 1916 - < 2455 mg/kg	Rat	ECHA	

## Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

## Sensitising effects

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 7 of 10

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

## 11.2. Information on other hazards

## **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d] Species	Source	Method
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol				
	Acute fish toxicity	LC50 175 mg/l	96 h Piscis	Manufacturer	

#### 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

No information available.

## 12.4. Mobility in soil

No information available.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

Avoid release to the environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

## **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## List of Wastes Code - residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 8 of 10

## List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances;

hazardous waste

## Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

## Inland waterways transport (ADN)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

#### Marine transport (IMDG)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

## Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

## 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## 14.6. Special precautions for user

No information available.

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): 0 %

Information according to 2012/18/EU

(SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

## **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing

mothers.



according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 9 of 10

Water hazard class (D): 1 - slightly hazardous to water

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

## Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method

## Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eve irritation.





according to Regulation (EC) No 1907/2006

# WP 2-K EPOXY-TURBO (Part B)

Revision date: 26.06.2023 Product code: 7011585101\_PartB Page 10 of 10

## **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)