Werkstatt-Produkte GmbH



Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WP Schraubensicherung mittelfest

Further trade names

WP Schraubensicherung mittelfest -> 40040 WP Schraubensicherung mittelfest -> 40041 WP Schraubensicherung mittelfest -> 40052

UFI: TKTU-S9JM-J000-AETM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

1.3. Details of the supplier of the safety data sheet

Company name: Werkstatt-Produkte GmbH Street: Hahnerberger Str. 175
Place: 42349 Wuppertal

Telephone: +49 (0) 202 - 495839-0 Telefax: +49 (0) 202 - 495839-10

e-mail: info@werkstatt-produkte.de Internet: www.werkstatt-produkte.de

1.4. Emergency telephone +49 (0) 89-19240 (24h) (deutsch und englisch)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

methacrylic acid, monoester with propane-1,2-diol

2,2'-ethylenedioxydiethyl dimethacrylate

alpha, alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide

2'-phenylacetohydrazide

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.



according to Regulation (EC) No 1907/2006

| WP Schraubensicherung mittelfest | | | | | |
|--|--|--------------|--|--|--|
| Revision date: 05.05.2023 | Product code: 40045 | Page 2 of 12 | | | |
| P102 | Keep out of reach of children. | | | | |
| P271 Use only outdoors or in a well-ventilated area. | | | | | |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. | | | | |

P405 Store locked up.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | | | | |
|------------|---|--|--|---------------|--|
| | EC No | Index No | REACH No | | |
| | Classification (Regulation (EC) No | 1272/2008) | • | | |
| 27813-02-1 | methacrylic acid, monoester with | propane-1,2-diol | | 25 - 40 % | |
| | 248-666-3 | | 01-2119490226-37 | | |
| | Eye Irrit. 2, Skin Sens. 1; H319 H | 317 | | | |
| 109-16-0 | 2,2'-ethylenedioxydiethyl dimetha | crylate | | 5 - 15 % | |
| | 203-652-6 | | 01-2119969287-21 | | |
| | Skin Sens. 1B; H317 | • | | | |
| 80-15-9 | alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide | | | <= 1,5 % | |
| | 201-254-7 | 617-002-00-8 | 01-2119475796-19 | | |
| | | e Tox. 4, Acute Tox. 4, Skin Corr. 1 331 H312 H302 H314 H318 H335 I | IB, Eye Dam. 1, STOT SE 3, STOT H373 H411 | | |
| 114-83-0 | 2'-phenylacetohydrazide | | | 0,1 - < 0,5 % | |
| | 204-055-3 | | | | |
| | Acute Tox. 3, Skin Irrit. 2, Eye Irrit | t. 2, Skin Sens. 1, STOT SE 3; H30 | 01 H315 H319 H317 H335 | | |
| 123-31-9 | 1,4-dihydroxybenzene; hydroquinone; quinol | | 0,01 - < 0,05 % | | |
| | 204-617-8 | 604-005-00-4 | 01-2119524016-51 | | |
| | Carc. 2, Muta. 2, Acute Tox. 4, Ey H341 H302 H318 H317 H400 H4 | ve Dam. 1, Skin Sens. 1B, Aquatic of | Acute 1, Aquatic Chronic 1; H351 | | |

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 3 of 12

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | | |
|----------|----------------|--|-----------------|--|--|
| | Specific Conc. | Limits, M-factors and ATE | | | |
| 109-16-0 | 203-652-6 | 2,2'-ethylenedioxydiethyl dimethacrylate | 5 - 15 % | | |
| | dermal: LD50 | = > 2000 mg/kg; oral: LD50 = > 2000 - 5000 mg/kg | | | |
| 80-15-9 | 201-254-7 | alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide | <= 1,5 % | | |
| | mg/kg; oral: L | E = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 1100 .D50 = 382 mg/kg | | | |
| 114-83-0 | 204-055-3 | 2'-phenylacetohydrazide | 0,1 - < 0,5 % | | |
| | oral: LD50 = 2 | oral: LD50 = 270 mg/kg | | | |
| 123-31-9 | 204-617-8 | 1,4-dihydroxybenzene; hydroquinone; quinol | 0,01 - < 0,05 % | | |
| | 1 | 367 mg/kg Aquatic Acute 1; H400: M=10 c 1; H410: M=1 | | | |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, Carbon dioxide (CO2), Dry extinguishing powder Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO2))

5.3. Advice for firefighters



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 4 of 12

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Keep away from: Food and feedingstuffs

Protect from direct sunlight.

Do not store together with: Oxidizing agent, Acids

Further information on storage conditions

storage temperature: < 25°C

M - en Print date: 20.07.2023



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 5 of 12

7.3. Specific end use(s)

Adhesives and sealants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

| CAS No | Name of agent | | | |
|--------------------------|--|----------------|----------|-------------------|
| DNEL type | | Exposure route | Effect | Value |
| 109-16-0 | 2,2'-ethylenedioxydiethyl dimethacrylate | | | |
| Worker DNEL, | long-term | inhalation | systemic | 48,5 mg/m³ |
| Worker DNEL, | long-term | dermal | systemic | 13,9 mg/kg bw/day |
| Consumer DN | EL, long-term | oral | systemic | 8,33 mg/kg bw/day |
| Consumer DN | EL, long-term | dermal | systemic | 8,33 mg/kg bw/day |
| Consumer DN | EL, long-term | inhalation | systemic | 14,5 mg/m³ |
| 123-31-9 | 1,4-dihydroxybenzene; hydroquinone; quinol | | | |
| Worker DNEL, | long-term | dermal | systemic | 3,33 mg/kg bw/day |
| Worker DNEL, | long-term | inhalation | systemic | 2,1 mg/m³ |
| Consumer DNEL, long-term | | oral | systemic | 0,6 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | systemic | 1,66 mg/kg bw/day |
| Consumer DN | EL, long-term | inhalation | systemic | 1,05 mg/m³ |

PNEC values

| CAS No | Name of agent | |
|--|--|---------------|
| Environmenta | Environmental compartment | |
| 109-16-0 | 2,2'-ethylenedioxydiethyl dimethacrylate | |
| Freshwater | | 0,016 mg/l |
| Marine water | | 0,002 mg/l |
| Freshwater s | ediment | 0,185 mg/kg |
| Marine sediment | | 0,018 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 1,7 mg/l |
| Soil 0,027 n | | 0,027 mg/kg |
| 123-31-9 | 1,4-dihydroxybenzene; hydroquinone; quinol | |
| Freshwater | | 0,00057 mg/l |
| Marine water | | 0,000057 mg/l |
| Freshwater sediment | | 0,0049 mg/kg |
| Marine sediment | | 0,00049 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 0,71 mg/l |
| Soil | | 0,00064 mg/kg |

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 6 of 12









Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN ISO 374)

By long-term hand contact

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: > 0,4mm

Permeation time (maximum wear duration): > 480 min.

By short-term hand contact

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material: > 0,4mm

Permeation time (maximum wear duration): > 480 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. (EN 340)

Respiratory protection

In case of inadequate ventilation wear respiratory protection. (EN 14387) Filter type: A

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid (Paste)
Colour: dark blue
Odour: characteristic
Odour threshold: not determined

Melting point/freezing point:

Boiling point or initial boiling point and

240 °C

boiling range:

Flammability:

Lower explosion limits:

upper explosion limits:

not determined

Flash point:

Auto-ignition temperature:

Decomposition temperature:

Non-flammable.

not determined

96 °C

> 400 °C

not determined



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 7 of 12

pH-Value: 3 - 4

Viscosity / kinematic: 1900 - 7500 mm²/s

(at 25 °C)

Water solubility: partially soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density:

Relative vapour density:

Particle characteristics:

not determined

1,0 - 1,1 g/cm³

not determined

not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

Reaction with: Oxidizing agent, Strong acid

10.4. Conditions to avoid

Protect against: Heat, Frost

10.5. Incompatible materials

Oxidizing agent, Strong acid, metals

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO2))

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 17417,0 mg/kg; ATE (dermal) 73333,3 mg/kg; ATE (inhalation vapour) 200,00 mg/l; ATE (inhalation dust/mist) 33,333 mg/l



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 8 of 12

| CAS No | Chemical name | | | | | |
|----------|--|-------------------|----------------|---------|--------------|----------|
| | Exposure route | Dose | | Species | Source | Method |
| 109-16-0 | 2,2'-ethylenedioxydiethyl dimethacrylate | | | | · | |
| | oral | LD50 5000 mg/l | > 2000 - kg | Rat | Manufacturer | |
| | dermal | LD50 mg/kg | > 2000 | Mouse | Manufacturer | |
| 80-15-9 | alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide | | | | | |
| | oral | LD50 | 382 mg/kg | Rat | Manufacturer | |
| | dermal | ATE mg/kg | 1100 | | | |
| | inhalation vapour | ATE | 3 mg/l | | | |
| | inhalation dust/mist | ATE | 0,5 mg/l | | | |
| 114-83-0 | 2'-phenylacetohydrazio | le | | | | |
| | oral | LD50 | 270 mg/kg | Mouse | RTECS | |
| 123-31-9 | 1,4-dihydroxybenzene; hydroquinone; quinol | | | | | |
| | oral | LD50 | 367 mg/kg | Rat | Manufacturer | OECD 401 |

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (methacrylic acid, monoester with propane-1,2-diol; 2,2'-ethylenedioxydiethyl dimethacrylate; 2'-phenylacetohydrazide; 1,4-dihydroxybenzene; hydroquinone; quinol)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (alpha,alpha-dimethylbenzyl hydroperoxide; cumene hydroperoxide)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 9 of 12

| CAS No | Chemical name | | | | | | |
|----------|--|---------------|-----------|-----------|------------------------------------|--------------|--------|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| 109-16-0 | 2,2'-ethylenedioxydiethyl | dimethacry | late | | | | |
| | Acute algae toxicity | ErC50 mg/l | > 100 | | Pseudokirchneriella subcapitata | Manufacturer | |
| 123-31-9 | 1,4-dihydroxybenzene; hydroquinone; quinol | | | | | | |
| | Acute algae toxicity | ErC50 | 0,033-0,3 | | Algae | Manufacturer | |
| | Acute crustacea toxicity | EC50 | 0,061-0,1 | | Daphnia magna (Big water flea) | Manufacturer | |

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|----------|--|---------|
| 123-31-9 | 1,4-dihydroxybenzene; hydroquinone; quinol | 0,59 |

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 10 of 12

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:

 14.2. UN proper shipping name:
 14.3. Transport hazard class(es):

 14.4. Packing group:

 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): <= 40 %

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under

the Maternity Protection Directive (92/85/EEC) for expectant or nursing

mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

M - en Print date: 20.07.2023



according to Regulation (EC) No 1907/2006

WP Schraubensicherung mittelfest

Revision date: 05.05.2023 Product code: 40045 Page 11 of 12

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure |
|--------------------|--------------------------|
| Eye Irrit. 2; H319 | Calculation method |
| Skin Sens. 1; H317 | Calculation method |
| STOT SE 3; H335 | Calculation method |

Relevant H and EUH statements (number and full text)

| H242 | Heating may cause a fire. |
|------|--|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| | |



according to Regulation (EC) No 1907/2006

| WP Schraubensicherung mittelfest | | | | |
|----------------------------------|--|---------------|--|--|
| Revision date: 05.05.2023 | Product code: 40045 | Page 12 of 12 | | |
| H335 | May cause respiratory irritation. | | | |
| H341 | Suspected of causing genetic defects. | | | |
| H351 | Suspected of causing cancer. | | | |
| H373 | May cause damage to organs through prolonged or repeated exposure. | | | |
| H400 | Very toxic to aquatic life. | | | |
| H410 | Very toxic to aquatic life with long lasting effects. | | | |
| H411 | Toxic to aquatic life with long lasting effects. | | | |

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

M - en Print date: 20.07.2023