

according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WP MW CA 2K-Kleber (Part A)

Further trade names

WP MW CA 2K-Kleber

UFI:

6F80-56G6-U30U-8SVS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

1.3. Details of the supplier of the safety data sheet

Company name:	Werkstatt-Produkte GmbH	
Street:	Hahnerberger Str. 175	
Place:	42349 Wuppertal	
Telephone:	+49 (0) 202 - 495839-0	Telefax:+49 (0) 202 - 495839-10
e-mail:	info@werkstatt-produkte.de	
Internet:	www.werkstatt-produkte.de	
1.4. Emergency telephone	+49 (0) 89-19240 (24h) (deutsch ur	nd englisch)
number:		0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling ethyl 2-cyanoacrylate

Signal word: Warning

Pictograms:



Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
present and easy to	do. Continue rinsing.



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 2 of 11

P337+P313	If eye irritation persists: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3. Other hazards

EUH202

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No	o 1272/2008)				
7085-85-0	ethyl 2-cyanoacrylate			80 - < 100 %		
	230-391-5	607-236-00-9	01-2119527766-29			
	Skin Irrit. 2, Eye Irrit. 2, STOT SE	3; H315 H319 H335				
123-31-9	1,4-dihydroxybenzene; hydroquin	one; quinol		< 0,1 %		
	204-617-8	604-005-00-4	04-005-00-4 01-2119524016-51			
	Carc. 2, Muta. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1B, Aquatic Acute 1, Aquatic Chronic 1; H351 H341 H302 H318 H317 H400 H410					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. Limits, M-factors and ATE				
7085-85-0	230-391-5	ethyl 2-cyanoacrylate			
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg STOT SE 3; H335: >= 10 - 100				
123-31-9	204-617-8	17-8 1,4-dihydroxybenzene; hydroquinone; quinol			
	oral: LD50 = 367 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician. Do not peel solidified product off the skin. Do not use force or solvents to remove product incrustations from affected skin areas.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 3 of 11

apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, Carbon dioxide (CO2), Dry extinguishing powder Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO2))

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 4 of 11

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Keep away from: Food and feedingstuffs Protect from direct sunlight. Do not store together with: Oxidizing agent

Further information on storage conditions

Store in a cool dry place. storage temperature: approx. 2 - 8 °C

7.3. Specific end use(s)

Adhesives and sealants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent					
DNEL type		Exposure route	Effect	Value		
7085-85-0	ethyl 2-cyanoacrylate					
Consumer DN	EL, acute	inhalation	local	9,25 mg/m ³		
Worker DNEL	, acute	inhalation	local	9,25 mg/m ³		
Consumer DN	EL, acute	inhalation	systemic	9,25 mg/m ³		
Worker DNEL	, acute	inhalation	systemic	9,25 mg/m ³		
Consumer DN	EL, long-term	inhalation	local	9,25 mg/m ³		
Worker DNEL	, long-term	inhalation	local	9,25 mg/m ³		
Consumer DN	EL, long-term	inhalation	systemic	9,25 mg/m ³		
Worker DNEL	, long-term	inhalation	systemic	9,25 mg/m ³		
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol					
Worker DNEL	, long-term	dermal	systemic	3,33 mg/kg bw/day		
Worker DNEL	, long-term	inhalation	systemic	2,1 mg/m ³		
Consumer DNEL, long-term		oral	systemic	0,6 mg/kg bw/day		
Consumer DNEL, long-term		dermal	systemic	1,66 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	1,05 mg/m³		



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 5 of 11

PNEC values

CAS No	Name of agent				
Environmental	Environmental compartment Value				
123-31-9	1,4-dihydroxybenzene; hydroquinone; quinol				
Freshwater	Freshwater 0,00057 mg/l				
Marine water 0,000057 mg/l					
Freshwater sediment 0,0049 mg/kg					
Marine sediment 0,00049 mg/kg					
Micro-organisms in sewage treatment plants (STP) 0,71 mg/l					
Soil 0,00064 mg/kg					

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls







Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN ISO 374)

By long-term hand contact Suitable material: Butyl caoutchouc (butyl rubber) Thickness of the glove material: > 0,4 mm Permeation time (maximum wear duration): > 480 min.

By short-term hand contact Suitable material: NBR (Nitrile rubber) Thickness of the glove material: > 0,4 mm Permeation time (maximum wear duration): > 480 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. (EN 14387) Filter type: A

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.





according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 6 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless, transparent	
Odour:	stinging	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and		169 - 187 °C
boiling range:		
Flammability:		Non-flammable.
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		103 °C
Auto-ignition temperature:		421 °C
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		not determined
Water solubility:		Reaction with: Water
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		not determined
Density:		not determined
Relative vapour density:		not determined
Particle characteristics:		not determined
9.2. Other information		

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reaction with: Oxidising agent, strong, Water, Amines, Alcohols, Alkali (lye)

10.4. Conditions to avoid

Protect against: Heat, Frost Protect from moisture.

10.5. Incompatible materials

Information is given in subsection 10.3.

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO2))

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.



WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 7 of 11

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
7085-85-0	ethyl 2-cyanoacrylate	ethyl 2-cyanoacrylate					
	oral	LD50 mg/kg	> 5000	Rat	Manufacturer	OECD 401	
	dermal	LD50 mg/kg	> 2000	Rabbit	Manufacturer	OECD 402	
123-31-9	1,4-dihydroxybenzene; ł	1,4-dihydroxybenzene; hydroquinone; quinol					
	oral	LD50	367 mg/kg	Rat	Manufacturer	OECD 401	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (ethyl 2-cyanoacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
123-31-9	1,4-dihydroxybenzene; h	1,4-dihydroxybenzene; hydroquinone; quinol					
	Acute algae toxicity	ErC50 0,033	72 h 3-0,3	Algae	Manufacturer		
	Acute crustacea toxicity	EC50 0,06		Daphnia magna (Big water flea)	Manufacturer		

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.



WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 8 of 11

Partition coefficient n-octanol/water

CAS No	No Chemical name				
123-31-9	23-31-9 1,4-dihydroxybenzene; hydroquinone; quinol				
BCF					
CAS No	Chemical name	BCF	Species	Source	
7085-85-0	ethyl 2-cyanoacrylate	0,776			

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 3334
14.2. UN proper shipping name:	Aviation regulated liquid, n.o.s. (ETHYLCYANACRYLATE)
14.3. Transport hazard class(es):	9
14.4. Packing group:	-
Classification code:	M11
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 3334
14.2. UN proper shipping name:	AVIATION REGULATED LIQUID, N.O.S. (ETHYLCYANACRYLATE)
14.3. Transport hazard class(es):	9
14.4. Packing group:	N-S



WP MW CA 2K-Kleber (Part A) Revision date: 29.06.2023 Product code: 40180 P Classification code: M11 Marine transport (IMDG) M11	age 9 of 11
Marine transport (IMDG)	
14.1. UN number or ID number: UN 3334	
14.2. UN proper shipping name: AVIATION REGULATED LIQUID, N.O.S. (ETHYLCYANACRYLATE)	
14.3. Transport hazard class(es): 9 14.4. Packing group: -	
Hazard label: 9	
9	
Special Provisions: 960	
Limited quantity: - Excepted quantity: -	
Encepted quantity.	
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number: UN 3334	
14.2. UN proper shipping name: AVIATION REGULATED LIQUID, N.O.S. (ETHYLCYANACRYLATE)	
14.3. Transport hazard class(es): 9	
14.4. Packing group:	
Hazard label: 9	
Ally.	
9	
Special Provisions: A27	
Limited quantity Passenger: 30 kg G	
Passenger LQ: Y964	
Excepted quantity: E1	
IATA-packing instructions - Passenger: 964 IATA-max. quantity - Passenger: 450 L	
IATA-hax. quality - Lassenger. 430 L IATA-packing instructions - Cargo: 964	
IATA-max. quantity - Cargo: 450 L	
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS: No	
14.6. Special precautions for user	
No information available.	
14.7. Maritime transport in bulk according to IMO instruments not applicable	
SECTION 15: Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
EU regulatory information	
Restrictions on use (REACH, annex XVII): Entry 3, Entry 75	
2010/75/EU (VOC): <= 10 %	
Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III):	

National regulatory information

M - en



WP MW CA 2K-Kleber (Part A)		
Revision date: 29.06.2023	Product code: 40180	Page 10 of 1
Employment restrictions:	Observe restrictions to employment for juveni work protection guideline' (94/33/EC). Observ the Maternity Protection Directive (92/85/EEC mothers.	e employment restrictions under
Water hazard class (D):	2 - obviously hazardous to water	
Additional information		
Observe in addition any nation	al regulations!	
15.2. Chemical safety assessment		
Chemical safety assessments	for substances in this mixture were not carried out.	
SECTION 16: Other information		
	ion and Authorization of Chemicals rstem of Classification, Labelling and Packaging of Ch rice el Level pncentration	emicals

vPvB: very persistent, very bioaccumulative

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part A)

Revision date: 29.06.2023

Product code: 40180

Page 11 of 11

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eve irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH202	Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part B)

Revision date: 29.06.2023

Product code: 40180_PartB

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WP MW CA 2K-Kleber (Part B)

Further trade names

WP MW CA 2K-Kleber

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

1.3. Details of the supplier of the safety data sheet

Company name:	Werkstatt-Produkte GmbH	
Street:	Hahnerberger Str. 175	
Place:	42349 Wuppertal	
Telephone:	+49 (0) 202 - 495839-0	Telefax:+49 (0) 202 - 495839-10
e-mail:	info@werkstatt-produkte.de	
Internet:	www.werkstatt-produkte.de	
<u>1.4. Emergency telephone</u> number:	+49 (0) 89-19240 (24h) (deutsch ur	nd englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. Resulting from the use of the product: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name		Quantity	
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1344-95-2	Silicic acid, calcium salt			1 - < 5 %
	215-710-8		01-2119990740-32	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1344-95-2	215-710-8	Silicic acid, calcium salt	1 - < 5 %
oral: LD50 = > 5000 mg/kg			

SECTION 4: First aid measures



WP MW CA 2K-Kleber (Part B)

Revision date: 29.06.2023

Product code: 40180_PartB

Page 2 of 8

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician. Do not peel solidified product off the skin. Do not use force or solvents to remove product incrustations from affected skin areas.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, Carbon dioxide (CO2), Dry extinguishing powder Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO2))

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part B)

Revision date: 29.06.2023

Product code: 40180_PartB

Page 3 of 8

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Keep away from: Food and feedingstuffs Protect from direct sunlight.

Further information on storage conditions

Store in a cool dry place. storage temperature: approx. 2 - 8 °C

7.3. Specific end use(s)

Adhesives and sealants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
1344-95-2	Silicic acid, calcium salt			
Worker DNEL,	long-term	inhalation	systemic	10 mg/m ³
Worker DNEL,	long-term	inhalation	local	10 mg/m ³
Consumer DN	EL, long-term	inhalation	systemic	5 mg/m³
Consumer DN	EL, long-term	inhalation	local	5 mg/m³



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part B)

Revision date: 29.06.2023

Product code: 40180_PartB

Page 4 of 8

PNEC values

CAS No	Name of agent	
Environmental	compartment	Value
1344-95-2 Silicic acid, calcium salt		
Micro-organisms in sewage treatment plants (STP) 100 mg/l		

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls







Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN ISO 374)



By long-term hand contact Suitable material: NBR (Nitrile rubber) Thickness of the glove material: > 0,4 mm Permeation time (maximum wear duration): > 120 min.

By short-term hand contact Suitable material: NBR (Nitrile rubber) Thickness of the glove material: > 0,4 mm Permeation time (maximum wear duration): > 480 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. (EN 14387) Filter type: A

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	white
Odour:	characteristic



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part B)

Revision date: 29.06.2023	Product code: 40180_PartB	Page 5 of 8
Odour threshold:	not determined	
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	195 °C	
Flammability:	Non-flammable.	
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	138 °C	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not determined	
Viscosity / kinematic:	not determined	
Water solubility: Solubility in other solvents not determined	not determined	
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 25 °C):	1,17 g/cm³	
Relative vapour density:	not determined	
Particle characteristics:	not determined	
9.2. Other information		
No information available.		

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reaction with: Oxidising agent, strong, Oxygen

10.4. Conditions to avoid

Protect against: Heat, Frost

10.5. Incompatible materials

Information is given in subsection 10.3.

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO2))

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
1344-95-2	Silicic acid, calcium salt					
	oral	LD50 mg/kg	> 5000	Rat	Manufacturer	



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part B)

Revision date: 29.06.2023

Product code: 40180_PartB

Page 6 of 8

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

Resulting from the use of the product: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part B)

Revision date: 29.06.2023

Product code: 40180_PartB

Page 7 of 8

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)						
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.					
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.					
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.					
14.4. Packing group:	No dangerous good in sense of this transport regulation.					
Inland waterways transport (ADN)						
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.					
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.					
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.					
14.4. Packing group:	No dangerous good in sense of this transport regulation.					
Marine transport (IMDG)						
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.					
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.					
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.					
14.4. Packing group:	No dangerous good in sense of this transport regulation.					
Air transport (ICAO-TI/IATA-DGR)						
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.					
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.					
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.					
14.4. Packing group:	No dangerous good in sense of this transport regulation.					
14.5. Environmental hazards						
ENVIRONMENTALLY HAZARDOUS:	No					
14.6. Special precautions for user						
No information available.						
14.7. Maritime transport in bulk according to IMO instruments						
not applicable						
SECTION 15: Regulatory information						
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture						
EU regulatory information						
2010/75/EU (VOC):	< 3 %					
Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)					
National regulatory information						

Water hazard class (D):

1 - slightly hazardous to water



according to Regulation (EC) No 1907/2006

WP MW CA 2K-Kleber (Part B)

Revision date: 29.06.2023

Product code: 40180_PartB

Page 8 of 8

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals **UN: United Nations** CAS: Chemical Abstracts Service DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Verv High Concern ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) IMDG: International Maritime Code for Dangerous Goods EmS: Emergency Schedules MFAG: Medical First Aid Guide IATA: International Air Transport Association ICAO: International Civil Aviation Organization For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Relevant H and EUH statements (number and full text)

Causes serious eye irritation.

H319

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)