

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WP Gehäusedichtmasse RT 300

UFI: UE6W-A9YQ-C00X-ESKT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives and sealants

1.3. Details of the supplier of the safety data sheet

Company name: Werkstatt-Produkte GmbH
Street: Hahnerberger Str. 175
Place: 42349 Wuppertal
Telephone: +49 (0) 202 - 495839-0 Telefax: +49 (0) 202 - 495839-10
e-mail: info@werkstatt-produkte.de
Internet: www.werkstatt-produkte.de

1.4. Emergency telephone number: +49 (0) 89-19240 (24h) (deutsch und englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 3; H229
Skin Corr. 1C; H314
Eye Dam. 1; H318
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Propyltriacetoxysilane
Methylsilanetriyl triacetate

Signal word: Danger

Pictograms:



Hazard statements

H229 Pressurised container: May burst if heated.
H314 Causes severe skin burns and eye damage.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 2 of 13

P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

< 1 % by mass of the contents are flammable.

2.3. Other hazards

The mixture contains the following substances fulfilling the PBT criteria according to REACH, annex XIII: octamethylcyclotetrasiloxane; [D4].

The mixture contains the following substances fulfilling the vPvB criteria according to REACH, annex XIII: octamethylcyclotetrasiloxane; [D4].

Resulting from the use of the product: Acetic acid. Provide adequate ventilation. Processing vapours can irritate the respiratory tracts, skin and eyes.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
17865-07-5	Propyltriacetoxysilane			1 - < 5 %
	241-816-9		01-2119966899-07	
	Skin Corr. 1B; H314 EUH071			
4253-34-3	Methylsilanetriyl triacetate			1 - < 5 %
	224-221-9		01-2119962266-32	
	Acute Tox. 4; Skin Corr. 1C; H302 H314 EUH014			
556-67-2	octamethylcyclotetrasiloxane; [D4]			< 0.1 %
	209-136-7	014-018-00-1	01-2119529238-36	
	Flam. Liq. 3; Repr. 2; Aquatic Chronic 1; H226 H361f H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
4253-34-3	224-221-9	Methylsilanetriyl triacetate	1 - < 5 %
	oral: LD50 = 1600 mg/kg		
556-67-2	209-136-7	octamethylcyclotetrasiloxane; [D4]	< 0.1 %
	inhalation: LC50 = 36 mg/l (dusts or mists); dermal: LD50 = 2375 mg/kg; oral: LD50 = 4800 mg/kg Aquatic Chronic 1; H410: M=10		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 3 of 13

skin reactions, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, Carbon dioxide (CO₂), Dry extinguishing powder
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pressurised container: May burst if heated. Vapours can form explosive mixtures with air.
Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO₂))

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 4 of 13

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use personal protection equipment.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Oxidizing agent

Further information on storage conditions

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
storage temperature: 10 - < 35°C

7.3. Specific end use(s)

Adhesives and sealants

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	
		20	50		STEL (15 min)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 5 of 13

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
17865-07-5	Propyltriacetoxysilane			
Worker DNEL, long-term		dermal	systemic	12,11 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	85,39 mg/m ³
Consumer DNEL, long-term		oral	systemic	6,05 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	6,05 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	21,06 mg/m ³
4253-34-3	Methylsilanetriyl triacetate			
Worker DNEL, acute		inhalation	local	61 mg/m ³
Worker DNEL, long-term		inhalation	local	31 mg/m ³
Consumer DNEL, long-term		inhalation	local	31 mg/m ³
Consumer DNEL, acute		inhalation	local	61 mg/m ³
556-67-2	octamethylcyclotetrasiloxane; [D4]			
Worker DNEL, long-term		inhalation	local	73 mg/m ³
Worker DNEL, long-term		inhalation	systemic	73 mg/m ³
Consumer DNEL, long-term		oral	systemic	3,7 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	13 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	13 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 6 of 13

PNEC values

CAS No	Name of agent	Value
Environmental compartment		
17865-07-5	Propyltriacetoxysilane	
Freshwater		0,02441 mg/l
Marine water		0,002441 mg/l
Freshwater sediment		0,01457 mg/kg
Marine sediment		0,001457 mg/kg
Micro-organisms in sewage treatment plants (STP)		10,55 mg/l
Soil		0,00336 mg/l
4253-34-3	Methylsilanetriyl triacetate	
Freshwater sediment		4,8 mg/kg
Marine sediment		0,48 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,9 mg/l
Soil		0,19 mg/kg
556-67-2	octamethylcyclotetrasiloxane; [D4]	
Freshwater		0,0015 mg/l
Marine water		0,00015 mg/l
Freshwater sediment		3 mg/kg
Marine sediment		0,3 mg/kg
Secondary poisoning		41 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,54 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN ISO 374)

By long-term hand contact

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: > 0,5mm

Permeation time (maximum wear duration): > 480 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 7 of 13

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Filter type: P2

Thermal hazards

No information available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid (Paste)
Colour:	red
Odour:	characteristic
Odour threshold:	not determined
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Non-flammable.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	not determined
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	practically insoluble
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	1,08 g/cm ³
Relative vapour density:	not determined
Particle characteristics:	not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Pressurised container: May burst if heated.

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Pressurised container: May burst if heated.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Pressurised container: May burst if heated.

Reaction with: Oxidising agent, strong

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 8 of 13

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Oxidizing agent

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide Carbon dioxide (CO₂))
Resulting from the use of the product: Acetic acid

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 62387,1 mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
4253-34-3	Methylsilanetriyl triacetate				
	oral	LD50 mg/kg 1600	Rat	Manufacturer	OECD 401
556-67-2	octamethylcyclotetrasiloxane; [D4]				
	oral	LD50 mg/kg 4800	Rat	Manufacturer	
	dermal	LD50 mg/kg 2375	Rat	Manufacturer	
	inhalation (4 h) dust/mist	LC50 36 mg/l	Rat	Manufacturer	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Resulting from the use of the product: Acetic acid. Processing vapours can irritate the respiratory tracts, skin and eyes.

In case of eye contact: The product is: slightly irritant but not relevant for classification. (By analogy. (Manufacturer) 92/69/EWG)

In case of skin contact: The product is: slightly irritant but not relevant for classification. (By analogy. (Manufacturer) 92/69/EWG)

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

11.2. Information on other hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 9 of 13

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
17865-07-5	Propyltriacetoxysilane					
	Acute fish toxicity	LC50 mg/l	108,89	96 h	Piscis	Manufacturer
4253-34-3	Methylsilanetriyl triacetate					
	Acute fish toxicity	LC50 mg/l	> 500	96 h	Danio rerio (zebrafish)	Manufacturer
	Acute algae toxicity	ErC50 mg/l	> 500	72 h	Pseudokirchneriella subcapitata	Manufacturer
	Acute crustacea toxicity	EC50 mg/l	> 500	48 h	Daphnia magna (Big water flea)	Manufacturer

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
17865-07-5	Propyltriacetoxysilane	1,23
4253-34-3	Methylsilanetriyl triacetate	- 2,4
556-67-2	octamethylcyclotetrasiloxane; [D4]	6,49

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The mixture contains the following substances fulfilling the PBT criteria according to REACH, annex XIII: octamethylcyclotetrasiloxane; [D4].

The mixture contains the following substances fulfilling the vPvB criteria according to REACH, annex XIII: octamethylcyclotetrasiloxane; [D4].

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 10 of 13

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.2



Classification code: 5A
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 3
 Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.2



Classification code: 5A
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.2
14.4. Packing group: -
 Hazard label: 2.2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 11 of 13



Special Provisions: 63 190 277 327 344 381 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, NON-FLAMMABLE
14.3. Transport hazard class(es): 2.2
14.4. Packing group: -
 Hazard label: 2.2



Special Provisions: A98 A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Pressurised container: May burst if heated.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
 octamethylcyclotetrasiloxane; [D4]

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 70, Entry 75

2010/75/EU (VOC): < 3 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

Regulation (EC) No. 842/2006 on certain fluorinated greenhouse gases: Contains fluorinated greenhouse gases.
 Propene, 1,3,3,3,-tetrafluoro-,(E)-

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 12 of 13

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
 REACH: Registration, Evaluation and Authorization of Chemicals
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
 UN: United Nations
 CAS: Chemical Abstracts Service
 DNEL: Derived No Effect Level
 DMEL: Derived Minimal Effect Level
 PNEC: Predicted No Effect Concentration
 ATE: Acute toxicity estimate
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%
 LL50: Lethal loading, 50%
 EL50: Effect loading, 50%
 EC50: Effective Concentration 50%
 ErC50: Effective Concentration 50%, growth rate
 NOEC: No Observed Effect Concentration
 BCF: Bio-concentration factor
 PBT: persistent, bioaccumulative, toxic
 vPvB: very persistent, very bioaccumulative
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships
 IBC: Intermediate Bulk Container
 VOC: Volatile Organic Compounds
 SVHC: Substance of Very High Concern
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Regulations concerning the international carriage of dangerous goods by rail
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
 IMDG: International Maritime Code for Dangerous Goods
 EmS: Emergency Schedules
 MFA: Medical First Aid Guide
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 3; H229	On basis of test data
Skin Corr. 1C; H314	Bridging principle "Aerosols"
Eye Dam. 1; H318	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WP Gehäusedichtmasse RT 300

Revision date: 19.06.2023

Product code: 40015

Page 13 of 13

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H361f	Suspected of damaging fertility.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH014	Reacts violently with water.
EUH071	Corrosive to the respiratory tract.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)