



Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 50990 WP Hohlraumversiegelung transparent 1L
- · **UFI**: ERUM-K0Q9-S00A-V99Q
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Corrosion inhibitors
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Werkstatt-Produkte GmbH Hahnerberger Str. 175 42349 Wuppertal
- 1.4 Emergency telephone number: Emergency number: +49 (0) 89 19240 Supplier: +49 (0) 202 - 495839-0

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

(Contd. of page 1)

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Calcium Sulfonate. May produce an allergic reaction.

· 2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with additions.

· Dangerous compor	nents:			
	Naphtha (petroleum), hydrotreated heavy			
	♠ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066			
	Naphtha (petroleum), hydrotreated heavy	10-<25%		
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066			
	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	5-<10%		
CAS: 61789-86-4	Calcium Sulfonate ♦ Skin Sens. 1B, H317 Specific concentration limit: Skin Sens. 1B; H317: C ≥ 10 %	5-<10%		
CAS: 154518-38-4	Mono- en di-alkyl(C11-14)esters van fosforzuur (onvertakt en vertakt)	1-<3%		
	📀 Eye Dam. 1, H318; 🕸 Aquatic Chronic 2, H411; 🗘 Skin Irrit. 2, H315			
CAS: 68526-86-3	CAS: 68526-86-3 alcohols, C11-14-iso-, C13-rich			
	🚯 Aquatic Acute 1, H400; Aquatic Chronic 2, H411			

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

(Contd. on page 3)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

(Contd. of page 3)

· Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

 \cdot 7.3 *Specific end use(s) No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs	· DNELs					
Naphtha (Naphtha (petroleum), hydrotreated heavy					
Oral	Long-term - systemic effects, general population	125 mg/kg bw/day (General Population)				
Dermal	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)				
	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)				
Inhalative	Long-term - systemic effects, worker	871 mg/m3 (Worker)				
	Long-term - systemic effects, general population	185 mg/m3 (General Population)				

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



Filter A

· Hand protection



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: ≥ 0.12 mm

· Penetration time of glove material

> 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

(Contd. of page 4)

· Eye/face protection



Tightly sealed goggles

· Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
Whitish
Recognisable
Not determined
Undetermined

· Boiling point or initial boiling point and boiling

range 136-164 °C (CAS: 64742-49-0 Naphtha (petroleum),

hydrotreated light)

· Flammability Flammable.

· Lower and upper explosion limit

Lower: 0,6 Vol % (Naphtha (petroleum), hydrotreated heavy)
 Upper: 7 Vol % (Naphtha (petroleum), hydrotreated heavy)
 Flash point: 29 °C (DIN 53213, CAS: 64742-49-0 Naphtha

(petroleum), hydrotreated light)

· Auto-ignition temperature: >200 °C (Naphtha (petroleum), hydrotreated heavy)

· Decomposition temperature: Not determined.

 $\cdot pH$ Mixture is non-soluble (in water).

· Viscosity:

· Kinematic viscosity At 40 °C >20,5 mm²/s · Dynamic At 20 °C: 360 mPas

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure At 20 °C: 5 hPa (CAS: 64742-49-0 Naphtha (petroleum),

hydrotreated light)

· Internal Pressure:

· Vapour pressure At 50 °C: 30 hPa

· Density and/or relative density

• **Density At 20 °C:** 0,861 g/cm³ (DIN 51757)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

 ⋅ VOC (EU):
 59,01 %

 ⋅ VOC (EU):
 508,1 g/l

 ⋅ VOCV:
 59,01 %

· Appearance:

· Form: Fluid

· Ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

(Contd. on page 6)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

(Contd. of page 5)

· Solvent content:

59.0 % · Organic solvents: · Water: 0.0 %

· Solids content: 42,1 % (DIN 53216)

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Void · Explosives · Flammable gases Void Void · Aerosols Void · Oxidising gases Void · Gases under pressure

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- $\cdot \textbf{10.5 Incompatible materials:} \ \textit{No further relevant information available}.$
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:				
Naphtha (Naphtha (petroleum), hydrotreated heavy				
Oral	LD50	>5.000 mg/kg (RAT)			
Dermal	LD50	>5.000 mg/kg (RABBIT)			
Inhalative	LC50/4 h	50/4 h 5.000 mg/l (RAT)			
Naphtha (j	Naphtha (petroleum), hydrotreated heavy				
Oral	LD50	>5.000 mg/kg (RAT)			
Dermal	LD50	>3.000 mg/kg (RAT)			

(Contd. on page 7)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

			(Contd. of page 6)		
Naphtha (Naphtha (petroleum), hydrotreated heavy				
Oral	LD50	>5.000 mg/kg (RAT)			
Dermal	LD50	>3.000 mg/kg (RAT)			
CAS: 1545	CAS: 154518-38-4 Mono- en di-alkyl(C11-14)esters van fosforzuur (onvertakt en vertakt)				
Oral	LD50	>2.000 mg/kg (rat)			
Dermal	LD50	>2.000 mg/kg (RABBIT)			

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- $\cdot \textbf{12.4 Mobility in soil} \ \textit{No further relevant information available}.$
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

(Contd. on page 8)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

Contd. of page 7)

• European waste catalogue

HP3 Flammable

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP14 Ecotoxic

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	UN1139
· 14.2 UN proper shipping name · ADR/RID/ADN · IMDG, IATA	1139 COATING SOLUTION COATING SOLUTION
· 14.3 Transport hazard class(es) · ADR/RID/ADN	
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids.
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
· 14.7 Maritime transport in bulk according to IM instruments	IO Not applicable.
· Transport/Additional information:	Tansport classification ADR/IMGD is based on packaging >30ltr(IMDG), >450ltr(ADR). For other packaging untis different classification can apply.





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

(Contd. of page 8)

•	\boldsymbol{A}	D	R	R	ID	A	D_{\cdot}	N
---	------------------	---	---	---	----	---	-------------	---

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1139 COATING SOLUTION, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 10)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

(Contd. of page 9)

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	59,0

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Version number of previous version: 20
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

(Contd. on page 11)





Printing date 18.08.2023 Version number 21 (replaces version 20) Revision: 01.08.2023

Trade name: 50990 WP Hohlraumversiegelung transparent 1L

(Contd. of page 10)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.